

# NTN NK28/20R needle roller bearings

LET OUR NTN NK28/20R needle roller bearings EXPERTS GET 184.15 mm da YOU THE PARTS YOU NEED.

da	184.15 mm
Da	419.999 mm
Ca	147.803 mm
A1	228.6 mm
A2	315.119 mm
S	4.763 mm
ba	103.188 mm
H	495.3 mm
H1	250.825 mm
H2	101.6 mm
J min.	666.75 mm
J max.	749.3 mm
J1	139.7 mm
L	869.95 mm
N1	41.275 mm
R1	163.512 mm
R2	50.8 mm
RG	1 NPT
PG	1/4 NPT
h	87.313 mm
Housing	SAF 640
Bearing	22340 CCK/W33
Adapter sleeve assembly	SNW 140×7.1/4

Stabilizing ring	SR-0-40
Labyrinth ring	2 x LOR 666
End plug (suffix Y)	EPR 21
Bearing limiting speed	1500 r/min
P60°	449 kN
P90°	271 kN
P120°	169 kN
P150°	151 kN
P180°	185 kN
Pa	82.7 kN
Mass pillow block	364 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	1017 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	3515.4 g