

NTN NK43/20R+IR38X43X20 needle roller bearings

What are the types of NTN NK43/20R+IR38X43X20 needle roller bearings 57,15 Bore Diameter (mm) ? 57.15×79.375×3.175 Size (mm) Manufacturing 79,375 Outer Diameter (mm) Service . Get Your Free, Instant price, design review.

Size (mm)	57.15×79.375×3.175
Bore Diameter (mm)	57,15
Outer Diameter (mm)	79,375
Width (mm)	3,175
d	57,15 mm
D	79,375 mm
T	3,175 mm
Ea	75,184 mm
Eb	59,94 mm
Weight	0,029 Kg
Basic dynamic load rating (C)	37,68 kN
Basic static load rating (C0)	177,04 kN
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.029
EAN	0605790192708
Product Group	B04144
Rolling Element	Needle Roller Bearing
Self Aligning	No
Component Description	Roller Assembly Only

Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Other Features	Single Row Two Piece Cage
Long Description	2-1/4" Bore 1; 2-1/4" Bore 2; 3-1/8" Outside Diameter; 1/8" Height; Needle Rolle
Inch – Metric	Inch
UNSPSC	31171500
Harmonized Tariff Code	8482.99.25.40
Noun	Roller Assembly
Keyword String	Thrust Needle
Manufacturer Item Number	NTA-3650
Weight / LBS	0.064
Height	0.125 Inch 3.175 Millimeter
Outside Diameter	3.125 Inch 79.375 Millimeter
Bore 1	2.25 Inch 57.15 Millimeter
Bore 2	2.25 Inch 57.15 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bearing No.	NTA-3650
Dc1	57.15
Dc	79.375
Dw	3.175
Ca	37.68
C0a	177.04
Cu	18.6
Limiting speeds(min-1)	5300

(Refer.)Mass(kg)	0.029
Washer designation	TRC-3650
d1	79.38
h(max)	2.41
h(min)	2.34
S(max)	57.15
S(min)	57.07
H	80.16
(Refer.)Washer mass(kg)	0.043