

# NTN NN4932C1NAP4 cylindrical roller bearings

NTN NN4932C1NAP4 cylindrical roller bearings Warehouse offers car parts and car accessories. We sell 52x25x15 Size (mm) discount online as well as 25 Outer Diameter (mm) cheap machinery parts.

Size (mm)	52x25x15
Bore Diameter (mm)	52
Outer Diameter (mm)	25
Width (mm)	15
d	25 mm
D	52 mm
B	15 mm
d1	34.35 mm
D2	46.21 mm
D3	49.73 mm
D4	57.9 mm
b	1.35 mm
C	2.46 mm
f	1.12 mm
r0	0.4 mm
r1,2 – min.	1 mm
da – min.	30.6 mm
Da – max.	46.4 mm
Db – min.	59 mm
ba – min.	1.5 mm
Ca – max.	3.58 mm

ra – max.	1 mm
Basic dynamic load rating – C	14.8 kN
Basic static load rating – C0	7.8 kN
Fatigue load limit – Pu	0.335 kN
Reference speed	28000 r/min
Limiting speed	18000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	14
Mass bearing	0.13 kg
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.137
EAN	7316577096616
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	25MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Fil
Other Features	Deep Groove   With Snap Ring
UNSPSC	31171504

Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6205 NR
Weight / LBS	0.302
Bore	0.984 Inch   25 Millimeter
Outer Race Width	0.591 Inch   15 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	2.047 Inch   52 Millimeter
d1 ≈	34.35 mm
D2 ≈	46.21 mm
r0 max.	0.4 mm
da min.	30.6 mm
Da max.	46.4 mm
Db min.	59 mm
ba min.	1.5 mm
Ca max.	3.58 mm
ra max.	1 mm
Basic dynamic load rating C	14.8 kN
Basic static load rating C0	7.8 kN
Fatigue load limit Pu	0.335 kN
Calculation factor kr	0.025
Calculation factor f0	14
Snap ring	SP 52