

NTN NU2236E cylindrical roller bearings

are a few brands you will find in our inventory. Find NTN NU2236E cylindrical roller bearings 0.0 Inventory to see what's in stock!

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	76.51
EAN	7316576670978
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Tapered Adapter Sleeve
Housing Style	4 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Steel
Expansion / Non-expansion	Expansion
Mounting Bolts	7/8 Inch
Relubricatable	Yes
Insert Part Number	22226 CCK/W33
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Inch
Other Features	Double Row Heavy Duty
Long Description	4 Bolt Pillow Block; 4-7/16" Bore; 6" Base to Center Height; Tapered Adapter Sleeve Mount;

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SAFS 22526
Weight / LBS	144
d	4.438 Inch 112.725 Millimeter
Bolt Spacing Minimum	14.625 Inch 371.475Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
D	8.125 Inch 206.375 Millimeter
B	6 Inch 152.4 Millimeter
Nominal Bolt Center to Center	15.3 Inch 389 Millimeter
Bolt Spacing Maximum	16 Inch 406.4Millimeter
da	112.713 mm
Da	230 mm
Ca	73.812 mm
A1	130.175 mm
A2	203.2 mm
S	4.763 mm
ba	57.944 mm
H	292.1 mm
H1	152.4 mm
H2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J1	82.55 mm
L	466.725 mm
N1	23.813 mm

R1	79.375 mm
R2	36.513 mm
RG	1/2 NPT
PG	1/4 NPT
h	60.325 mm
Housing	SAFS 526
Bearing	22226 EK
Adapter sleeve assembly	SNW 26×4.7/16
Stabilizing ring	SR-26-0
Labyrinth ring	2 x LOR 117
End plug (suffix Y)	EPR 15
Bearing limiting speed	3600 r/min
P60°	308 kN
P90°	185 kN
P120°	125 kN
P150°	118 kN
P180°	151 kN
Pa	24.9 kN
Mass pillow block	83.9 kg
Cap bolt	3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	0.875 in
Initial grease fill	382.73 g