

NTN RNU0314ZZ cylindrical roller bearings

Can't find what you're looking for NTN RNU0314ZZ cylindrical roller bearings 980x600x300 Size (mm) ? Our 600 Outer Diameter (mm) expert Representatives be in contact with you shortly!

| | |
|-------------------------------|-------------|
| Size (mm) | 980x600x300 |
| Bore Diameter (mm) | 980 |
| Outer Diameter (mm) | 600 |
| Width (mm) | 300 |
| d | 600 mm |
| D | 980 mm |
| B | 300 mm |
| d2 | 705 mm |
| D1 | 871 mm |
| s1 | 26.1 mm |
| r1,2 – min. | 7.5 mm |
| da – min. | 632 mm |
| da – max. | 704 mm |
| Da – min. | 827 mm |
| Da – max. | 948 mm |
| Ca – min. | 5.1 mm |
| ra – max. | 6 mm |
| Basic dynamic load rating – C | 10200 kN |
| Basic static load rating – C0 | 18000 kN |
| Fatigue load limit – Pu | 1140 kN |
| Reference speed | 430 r/min |
| Limiting speed | 600 r/min |

| | |
|-------------------------------|----------|
| Factor – k2 | 0.107 |
| d2 ≈ | 705 mm |
| D1 ≈ | 871 mm |
| s1 max. | 26.1 mm |
| r1,2 min. | 7.5 mm |
| Da min. | 827 mm |
| Da max. | 948 mm |
| Ca min. | 5.1 mm |
| ra max. | 6 mm |
| Basic dynamic load rating C | 10200 kN |
| Basic static load rating C0 | 18000 kN |
| Fatigue load limit Pu | 1140 kN |
| Misalignment factor k1 | 0 |
| Operating clearance factor k2 | 0.107 |
| Mass bearing | 901 kg |