

# PFI PHU2032 angular contact ball bearings

Question PFI PHU2032 angular contact ball bearings ? Find what you need 0.0 Inventory faster SKF Manufacturer Name by entering your information .

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | SKF  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 8.612  |
| EAN                       | 7316570219241  |
| Product Group             | B04311   |
| Internal Clearance        | C3-Loose   |
| Mounting Method           | Adapter Mount  |
| Rolling Element           | Spherical Roller Bearing   |
| Bore Profile              | Tapered  |
| Cage Material             | Steel  |
| Enclosure                 | Open   |
| Number of Rows of Rollers | Double Row   |
| Relubricatable            | Yes  |
| Withdrawal Sleeve         | AHX2318 (Specify bore)   |
| Withdrawal Nut            | KM21   |
| Inch – Metric             | Metric   |
| Long Description          | 90MM Tapered Bore; 190MM Outside Diameter; 64MM Width; C3-Loose Clearance; Adapter Mount; Double Row |

|                              |  |
|------------------------------|--|
| Other Features               | Order adapter or withdrawal sleeve or nut separately. Others may be available          |
| UNSPSC                       | 31171510   |
| Harmonized Tariff Code       | 84823080   |
| Noun                         | Bearing  |
| Keyword String               | Spherical  |
| Weight / LBS                 | 18.783   |
| d                            | 3.543 Inch   90 Millimeter   |
| Adapter Part Number          | SNW118 H2318 HA2318 HE2318<br>(Specify Bore) Inch   H2318<br>(Specify bore) Millimeter |
| B                            | 2.52 Inch   64 Millimeter  |
| D                            | 7.48 Inch   190 Millimeter   |
| bore diameter:               | 90 mm  |
| maximum rpm:                 | 3600 RPM   |
| outside diameter:            | 190 mm   |
| operating temperature range: | Maximum of +390 °F   |
| overall width:               | 4.3800 in  |
| cage material:               | Steel  |
| bore type:                   | Tapered 1:12   |
| bearing material:            | Steel  |
| outer ring type:             | Not Split  |
| cage type:                   | Inner Ring Guided  |
| internal clearance:          | C3   |
| precision rating:            | Not Rated  |
| closure type:                | Open   |
| finish/coating:              | Uncoated   |
| lubrication hole type:       | Lubrication Groove & Hole  |
| outer ring width:            | 64 mm  |

|                        |        |
|------------------------|--------|
| dynamic load capacity: | 610 kN |
| fillet radius:         | 2.5 mm |
| static load capacity:  | 695 kN |
| series:                | 223    |