

# Precision 9inch Slewing Drive PE9 for Truck Crane

Precision 9inch Slewing Drive PE9 for Truck Crane Deal is your source for OEM and accessories. We sell Genuine at discount prices. 25x62x25.4 Size (mm)

Size (mm)	25x62x25.4
Bore Diameter (mm)	25
Outer Diameter (mm)	62
Width (mm)	25.4
d	25 mm
D	62 mm
B	25.4 mm
C	25.4 mm
Angle ( $\alpha$ )	30 °
r min.	1.1 mm
Weight	0.340 Kg
Basic dynamic load rating (C)	32 kN
Basic static load rating (C0)	21,6 kN
(Grease) Lubrication Speed	7300 r/min
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0.341
EAN	4991893604221
Product Group	B00152
Enclosure	Open
Flush Ground	No

Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	20 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	25MM Bore; 62MM Outside Diameter; 25.4MM Width; Open; No Flush Ground; Ball Bearing; Double Row of B
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	5305 BNLS
Weight / LBS	0.75
Outside Diameter	2.441 Inch   62 Millimeter
Width	1 Inch   25.4 Millimeter
Bore	0.984 Inch   25 Millimeter
Configuration	Double Row
Bore Type	Cylindrical Bore
Bore Size	25 mm
Fillet Radius/Chamfer	1.1 mm
Dynamic Load Rating	32,000 N
Static Load Rating	21,600 N
Limiting Speed – Grease	7,300 rpm

Limiting Speed – Oil	10,000 rpm
Radial Clearance	0.005 to 0.020 mm
da	32 mm55 mm
Dx	68.5 mm
ra	1 mm
Cy	4.7 mm