RHP LJT15 angular contact ball bearings

Browse RHP LJT15 angular contact ball bearings Categories in the Manufacturers Online Free. including Mounted Bearing Engineering Group .

| Engineering Group | Mounted Bearing |
|--------------------------|-----------------|
| Shaft Size | 2-3/16 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | QVVMC13V203SB |
| Locking Style | Double V-Lock |
| Weight | 12 lb |
| Housing Style | Cartridge |
| UPC Code | 0883450150910 |
| Dimension A | 0.530 in |
| Dimension B | 0.906 in |
| Dimension C | 3.16 in |
| Dimension D | 0.188 in |
| Dimension F | 5.0000 in |
| Dimension G | 2.640 in |
| Dimension L Exp | 3.46 in |
| Dimension L Fix | 3.38 in |
| Dimension RVV | 0.86 in |
| Dimension SVV | 4.24 in |
| C — Dynamic Load (Basic) | 46400 lb |
| C0 — Static Load | 48600 lb |
| e – Geometry Factor | 0.24 |
| Y1 – Geometry Factor | 2.79 |

| Y2 – Geometry Factor | 4.15 |
|-------------------------------------|-----------|
| Oil Lubrication — M/N Seal | 1800 rpm |
| Oil Lubrication – T Seal | 3200 rpm |
| Oil Lubrication – B/C/O Seal | 1500 rpm |
| Grease Lubrication - M/N Seal | 1800 rpm |
| Grease Lubrication – T Seal | 2800 rpm |
| Grease Lubrication – B/C/O Seal | 1500 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0015 in |
| Eng Internal Radial Clearance – Min | 0.0030 |
| Eng Internal Radial Clearance – Max | 0.0037 |
| Pre Install Clearance Min | 0.0030 in |
| Pre Install Clearance Max | 0.0037 in |