

RHP MJ7.1/2 deep groove ball bearings

We work closely with our RHP MJ7.1/2 deep groove ball bearings manufacturing partners to bring 90 mm Da the best value to 42.862 mm da customers.

da	42.862 mm
Da	90 mm
Ca	29.794 mm
A1	60.325 mm
A2	165.1 mm
S	3.572 mm
ba	26.194 mm
H	121.841 mm
H1	63.5 mm
H2	23.813 mm
J min.	165.1 mm
J max.	177.8 mm
L	209.55 mm
N1	15.875 mm
R1	30.163 mm
R2	14.287 mm
RG	1/8 NPT
PG	1/8 NPT
h	27.781 mm
Housing	SAF 510
Bearing	22210 EK
Adapter sleeve assembly	SNW 10×1.11/16

Stabilizing ring	SR-10-0
Taconite seal	TER 20
End plug (suffix Y)	EPR 4
Max. speed for Taconite seal	1800 r/min
P60°	28.9 kN
P90°	17.3 kN
P120°	11.1 kN
P150°	9.79 kN
P180°	12.5 kN
Pa	3.47 kN
Mass pillow block	6.19 kg
Cap bolt	2 x 7/16-14 UNC
Cap bolt recommended tightening torque	61 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.5 in
Initial grease fill	31.185 g