

# RHP MRJ8 cylindrical roller bearings

RHP MRJ8 cylindrical roller bearings 14 mm B Industries and 12 mm d Applications ? We sell discount online as well as cheap machinery parts.

d	12 mm
D	32 mm
B	14 mm
rs min	0.6 mm
Radial clearance class	C3
Mass	0.04 kg
Dynamic load, C	6.1 kN
Static load, C <sub>0</sub>	2.75 kN
Fatigue limit load, C <sub>u</sub>	0.13 kN
f <sub>0</sub>	12.7
N <sub>lim</sub> (grease)	16,000 rpm
Min operating temperature, T <sub>min</sub>	-25 °C
Max operating temperature, T <sub>max</sub>	110 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.71 Hz
Characteristic outer ring frequency, BPF <sub>0</sub>	2.62 Hz
Characteristic inner ring frequency, BPFI	4.38 Hz
da min	16 mm
Da max	28 mm

ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.051
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	12MM Bore; 32MM Outside Diameter; 14MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.1212

Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	1.26 Inch   32 Millimeter
Outer Race Width	0.551 Inch   14 Millimeter
Bore	0.472 Inch   12 Millimeter