

# Ruville 6516 wheel bearings

100% TIMKEN Manufacturer Name Authentic. Ruville 6516 wheel bearings N/A Minimum Buy Quantity Highest Quality. Certified Supplier. 0.0 Inventory

|  |               |
|--|---------------|
| Inventory                                | 0.0           |
| Manufacturer Name                        | TIMKEN        |
| Minimum Buy Quantity                     | N/A           |
| EAN                                      | 0087796156470 |
| Weight / US pound                        | 0.01          |
| Product Group                            | B04311        |
| Design Unit                              | METRIC        |
| Bore Taper                               | 1/12          |
| Bearing Weight                           | 240.000 Kg    |
| Cage Type                                | EJ            |
| UPC Code                                 | 087796156470  |
| Cage Material                            | Steel         |
| Superseded Part                          | 23264KCJW906A |
| d – Bore                                 | 320.000 mm    |
| D – Outer Diameter                       | 580.000 mm    |
| B – Inner Ring Width                     | 208 mm        |
| B – Outer Ring Width                     | 208.000 mm    |
| R – Inner Ring To Clear Radius1          | 4.000 mm      |
| r – Outer Ring To Clear Radius2          | 4.000 mm      |
| da – Inner Ring Backing Diameter         | 377.000 mm    |
| Da – Outer Ring Backing Diameter         | 516.000 mm    |
| C0 – Static Radial Rating                | 7090000 N     |
| C1(2) – Dynamic Radial Rating (Two-Rows) | 4770000 N     |

|   |        |
|---|--------|
| e – ISO Factor <sup>3</sup>                       | 0.34   |
| Y <sub>0</sub> – ISO Factor <sup>4</sup>          | 1.98   |
| Y <sub>1</sub> – ISO Factor <sup>5</sup>          | 2.94   |
| Y <sub>2</sub> – ISO Factor <sup>6</sup>          | 1.93   |
| Reference Thermal Speed Rating (Grease)           | 490    |
| Reference Thermal Speed Rating (Oil) <sup>7</sup> | 530    |
| C <sub>g</sub> – Geometry Factor <sup>8</sup>     | 0.1354 |