

# Ruville 8402 wheel bearings

Can't find what you're looking for Ruville 8402 wheel bearings ? Our expert Representatives be 2.0 Inventory in contact with you shortly!

|                           |  |
|---------------------------|--|
| Inventory                 | 2.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 15.18 lb   |
| EAN                       | 0087796061798  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Eccentric Collar   |
| Housing Style             | 4 Bolt Square Flange Block   |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 41/64 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | G1211KRRB  |
| Seals                     | Double Land Riding Rubber Contact  |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | No Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 4 Bolt Square Flange Block;<br>2-11/16" Bore; 8.3" Bolt<br>Circle; 5-7/8" Bolt Spacing; 1<br>P |

|                                       |   |
|---------------------------------------|---|
| Other Features                        | Single Row   Normal Duty   With Set Screw |
| UNSPSC                                | 31171501                                  |
| Harmonized Tariff Code                | 8483.20.40.40                             |
| Noun                                  | Bearing                                   |
| Keyword String                        | Flanged                                   |
| Manufacturer Item Number              | RCJ 2 11/16                               |
| Weight / LBS                          | 15.18                                     |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter                     |
| D                                     | 2.688 Inch   68.275 Millimeter            |
| Bolt Spacing                          | 5.875 Inch   149.225 Millimeter           |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter                     |
| d                                     | 2.688 Inch   68.275 Millimeter            |
| Nominal Bolt Circle Diameter Round    | 8.3 Inch   211 Millimeter                 |
| Shaft Size d                          | 2 11/16 in                                |
| Dimension D                           | 6.0 in                                    |
| Dimension E                           | 3.555 in                                  |
| Inside Ring Outside Diameter          | 3.791 in                                  |
| Series                                | Industrial                                |
| Seal Type                             | Shroud Seal                               |
| Total Length L                        | 187.3 mm                                  |
| Housing Width A                       | 2.500 in                                  |
| Bolt Hole Spacing J                   | 149.2 mm                                  |
| Bolt Hole Size N                      | 16 mm                                     |
| Flange Thickness A1                   | 19.1 mm                                   |
| Center of Bearing from Housing End A2 | 45.1 mm                                   |

|   |                                     |
|---|-------------------------------------|
| Inside Ring Width B                     | =Bearings1_Inside Ring Width=<br>mm |
| Bolt Size                               | M16                                 |
| Center of Bearing from<br>Bearing End S | 45.1 mm                             |
| Static Load Rating                      | 9890 lbf                            |
| Dynamic Load Rating                     | 15500 lbf                           |