

SCE47 INA nB 24300 1/min / Reference speed 6.35×11.112×11.112mm Needle roller bearings

| | |
|---------------------------|---|
| Category | Needle Non Thrust Roller Bearings |
| BDI Inventory | 3600.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| EAN | 4012802070361 |
| Product Group – BDI | B04144 |
| Rolling Element | Needle Roller Bearing |
| Component | Roller Assembly with Outer Ring – No Inner Ring |
| Enclosure | Open |
| Self Aligning | No |
| Retainer | Yes |
| Number of Rows of Rollers | Single Row |
| Separable | No |
| Closed End | No |
| Inch – Metric | Inch |
| Relubricatable | No |
| Thrust Bearing | No |

| | |
|--------------------------|---|
| Long Description | 1/4" Bore; 7/16" Outside Diameter; 7/16" Width; Needle Roller Bearing; Roller Assembly with Outer Ring – No Inner Ring; Open; Not Self Aligning; Retainer; Single Row of Rollers; Not Separable; Not Closed End; Not Relubricatable |
| Other Features | 2 Rib Outer Ring Drawn Cup Bearing Steel Cage |
| Category – BDI | Needle Non Thrust Roller Bearing |
| UNSPSC | 31171512 |
| Harmonized Tariff Code | 8482.99.65.30 |
| Noun | Roller Assembly with Outer Ring |
| Keyword String | Bearing Needle |
| Manufacturer URL | http://www.ina.com |
| Manufacturer Item Number | SCE47 |
| Weight / LBS | 0.009 |
| Width | 0.438 Inch 11.125 Millimeter |
| Bore | 0.25 Inch 6.35 Millimeter |
| Outside Diameter | 0.438 Inch 11.125 Millimeter |
| Bearing number | SCE47 |
| Size (mm) | 6.35×11.112×11.112 |
| Brand | INA |
| Bore Diameter (mm) | 6.35 |
| Outer Diameter (mm) | 11.112 |
| Width (mm) | 11.112 |
| F _w | 1/4 inch |
| F _w | 6.35 mm |
| D | 0.437 inch |

| | |
|----------|---|
| D | 11.112 mm |
| C | 0.437 inch |
| C | 11.112 mm |
| m | 0.009 lbs / Weight |
| m | 4 g / Weight |
| C_r | 920 lbf / Dynamic load rating (radial) |
| C_r | 4100 N / Dynamic load rating (radial) |
| C_{0r} | 870 lbf / Static load rating (radial) |
| C_{0r} | 3900 N / Static load rating (radial) |
| n_G | 35000 1/min / Limiting speed |
| n_B | 24300 1/min / Reference speed |