

# SIGMA 7213-B angular contact ball bearings

SIGMA 7213-B angular contact ball bearings Warehouse offers car parts and 40 Bore Diameter (mm) car accessories. We sell discount online as well as cheap 40x68x15 Size (mm) machinery parts.

Size (mm)	40x68x15
Bore Diameter (mm)	40
Outer Diameter (mm)	68
Width (mm)	15
d	40 mm
D	68 mm
B	15 mm
C	15 mm
rn	0,5 mm
r min.	1 mm
da min.	45 mm
da max	47 mm
Da max.	63 mm
ra max.	1 mm
Weight	0,19 Kg
Basic dynamic load rating (C)	16,8 kN
Basic static load rating (C0)	11,5 kN
(Grease) Lubrication Speed	10 000 r/min
Inventory	6.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A

Weight / Kilogram	0.2
EAN	4547359003888
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6008ZZ
Weight / LBS	0.41
Outside Diameter	2.677 Inch   68 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.591 Inch   15 Millimeter
Bore	1.575 Inch   40 Millimeter
bore diameter:	40 mm
precision rating:	ISO Class 0
outside diameter:	68 mm

finish/coating:	Uncoated
overall width:	15 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	15 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	15 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	10000 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	6100 RPM
dynamic load capacity:	16800 N
series:	60
static load capacity:	11500 N
manufacturer product page:	<a href="#">Click here</a>