

SIGMA ELU 20 0544 thrust ball bearings

SIGMA ELU 20 0544 thrust ball bearings, Units and Housings CAD models , Manufacturing 63.500 Bore Diameter (mm) Service 63.500 mm Fw . Get Your Free.

Bore Diameter (mm)	63.500
Outer Diameter (mm)	73.025
Fw	63.500 mm
Ew	73.025 mm
Bc	25.40 mm
Weight	0.105 Kg
Basic dynamic load rating (C)	61,5 kN
Basic static load rating (C0)	117 kN
(Grease) Lubrication Speed	4 000 r/min
Dw	4.76 mm
Lw	21.3 mm
Mass	0.1 kg
Cr	61.5 kN
C0r	117 kN
Nlim (grease)	4,000 rpm
Nlim (oil)	6,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	14.26 Hz
Characteristic outer ring frequency, BPF0	13.49 Hz
Characteristic inner ring frequency, BRFI	15.51 Hz

b	25.4 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.123
Product Group	B04144