SIGMA ESA 25 0955 thrust ball bearings

SIGMA ESA 25 0955 thrust ball bearings with easy-to-use 2-1/2 in base width: parts graphics, giving you the 1.9375 in d ability to check parts availability, pricing, examine remanufactured options.

d1.9375 inbase width:2-1/2 inoverall length:8.8750 inexpansion type:Expansion Bearing (Floating)overall height:4.5625 infinish/coating:Powder Coatedmounting:Two-Bolt BaseB3-1/8 inbearing type:Spherical Rollerseal type:Labyrinthbore type:Roundradial dynamic load capacity:21200 lbhousing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:2150 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:400D6-1/16 to 7-1/4 in		
overall length:8.8750 inexpansion type:Expansion Bearing (Floating)overall height:4.5625 infinish/coating:Powder Coatedmounting:Two-Bolt BaseB3-1/8 inbearing type:Spherical Rollerseal type:Labyrinthbore type:Roundradial dynamic load capacity:21200 lbhousing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	d	1.9375 in
expansion type:Expansion Bearing (Floating)overall height:4.5625 infinish/coating:Powder Coatedmounting:Two-Bolt BaseB3-1/8 inbearing type:Spherical Rollerseal type:Labyrinthbore type:Roundradial dynamic load capacity:21200 lbhousing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:2150 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	base width:	2-1/2 in
overall height:4.5625 infinish/coating:Powder Coatedmounting:Two-Bolt BaseB3-1/8 inbearing type:Spherical Rollerseal type:Labyrinthbore type:Roundradial dynamic load capacity:21200 lbhousing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	overall length:	8.8750 in
finish/coating:Powder Coatedmounting:Two-Bolt BaseB3-1/8 inbearing type:Spherical Rollerseal type:Labyrinthbore type:Roundradial dynamic load capacity:21200 lbhousing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	expansion type:	Expansion Bearing (Floating)
mounting:Two-Bolt BaseB3-1/8 inbearing type:Spherical Rollerseal type:Labyrinthbore type:Roundradial dynamic load capacity:21200 lbhousing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:2150 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	overall height:	4.5625 in
B3-1/8 inbearing type:Spherical Rollerseal type:Labyrinthbore type:Roundradial dynamic load capacity:21200 lbhousing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:2150 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	finish/coating:	Powder Coated
bearing type:Spherical Rollerseal type:Labyrinthbore type:Roundradial dynamic load capacity:21200 lbhousing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:2150 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	mounting:	Two-Bolt Base
seal type:Labyrinthbore type:Roundradial dynamic load capacity:21200 lbhousing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:2150 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	В	3-1/8 in
bore type:Roundradial dynamic load capacity:21200 lbhousing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:2150 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	bearing type:	Spherical Roller
radial dynamic load capacity: 21200 lb housing construction: Solid Pillow Block radial static load capacity: 33200 lb base to bore centerline: 2.2500 in maximum rpm: 2150 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Concentric Collar series: 400	seal type:	Labyrinth
housing construction:Solid Pillow Blockradial static load capacity:33200 lbbase to bore centerline:2.2500 inmaximum rpm:2150 RPMhousing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	bore type:	Round
radial static load capacity: 33200 lb base to bore centerline: 2.2500 in maximum rpm: 2150 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Concentric Collar series: 400	radial dynamic load capacity:	21200 lb
base to bore centerline: 2.2500 in maximum rpm: 2150 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Concentric Collar series: 400	housing construction:	Solid Pillow Block
maximum rpm: 2150 RPM housing material: Cast Iron lubrication type: Lubrication Fitting locking device: Concentric Collar series: 400	radial static load capacity:	33200 lb
housing material:Cast Ironlubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	base to bore centerline:	2.2500 in
Iubrication type:Lubrication Fittinglocking device:Concentric Collarseries:400	maximum rpm:	2150 RPM
locking device: Concentric Collar series: 400	housing material:	Cast Iron
series: 400	lubrication type:	Lubrication Fitting
	locking device:	Concentric Collar
D 6-1/16 to 7-1/4 in	series:	400
	D	6-1/16 to 7-1/4 in

standards me	et:	ANSI/A
--------------	-----	--------