

SIGMA MR-28 needle roller bearings

SIGMA MR-28 needle roller bearings, Units and Housings CAD models , 0.0 Inventory Manufacturing Service . Get Your N/A Minimum Buy Quantity Free.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.274
EAN	7316571004976
Product Group	B00152
Mounting Method	Shaft
Enclosure	2 Seals
Rolling Element	Ball Bearing
Cage Material	Polyamide
Precision Class	ABEC 1 ISO P0
Internal Clearance	C0-Medium
Number of Rows of Balls	Double Row
Other Features	Allowable Misalignment 2.5 Deg Lubricated
Long Description	30MM Bore; Shaft Mount; 62MM Outside Diameter; 20MM Inner Race Width; 20MM Outer Race Width; 2 Seals
Inch – Metric	Metric
UNSPSC	31171532
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing

Keyword String	Self Aligning
d	1.181 Inch 30 Millimeter
D	2.441 Inch 62 Millimeter
Inner Race Width	0.787 Inch 20 Millimeter
Outer Race Width	0.787 Inch 20 Millimeter
bore diameter:	30 mm
dynamic load capacity:	3507 lbf
outside diameter:	62 mm
static load capacity:	1045 lbf
overall width:	20 mm
bearing material:	Steel
bore type:	Straight
cage material:	Polyamide
closure type:	Double Sealed
finish/coating:	Uncoated
internal clearance:	C0
maximum misalignment:	2.5 °
operating temperature range:	0 °F to 185 °F
application:	Metal manufacturing, Paper mills, Steel mills—plate, slab, strip, blast furnace, Overhead cran