

# SIGMA NUP 2205 cylindrical roller bearings

Shop SIGMA NUP 2205 cylindrical roller bearings 25 mm B huge online discount inventory. and Import machinery parts your 45 mm d car needs with Free Shipping and Free Extended Warranty. 100 mm D

d	45 mm
D	100 mm
B	25 mm
rs min	1.5 mm
Radial clearance class	C3
Mass	0.81 kg
Dynamic load, C	53 kN
Static load, C0	32 kN
Fatigue limit load, Cu	1.45 kN
f0	13.1
Nlim (grease)	4,700 rpm
Min operating temperature, Tmin	-10 °C
Max operating temperature, Tmax	160 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4 Hz
Characteristic outer ring frequency, BPF0	3.06 Hz
Characteristic inner ring frequency, BRFI	4.94 Hz
da min	53 mm

da max	61.5 mm
Da max	92 mm
ra max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.83
Product Group	B04270
Enclosure	2 Seals
Precision Class	ABEC 3   ISO P6
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	0 Degree
Preload	None
Raceway Style	Not Applicable
Cage Material	Steel
Rolling Element	Ball Bearing
Enclosure Type	Contact Seal
Flush Ground	No
Inch – Metric	Metric
Other Features	Single Row   Deep Groove   C3 Clearance   Prelubricant
Long Description	45MM Bore; 100MM Outside Diameter; 25MM Width; 2 Seals Enclosure; ABEC 3   ISO P6 Precision; Steel B
UNSPSC	31171502
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball Deep Groove

Bore	1.772 Inch   45 Millimeter
Outside Diameter	3.937 Inch   100 Millimeter
Width	0.984 Inch   25 Millimeter