

SKF 23032 CCK/W33 spherical roller bearings

SKF 23032 CCK/W33 spherical roller bearings SEARCH – Whether it's agriculture or 30 Bore Diameter (mm) construction 30x80x100 Size (mm) equipment your working on, Has the you need.

| | |
|---|-----------|
| Size (mm) | 30x80x100 |
| Bore Diameter (mm) | 30 |
| Outer Diameter (mm) | 80 |
| Width (mm) | 100 |
| D | 80 mm |
| d | 30 mm |
| B | 100 mm |
| C | 35 mm |
| B1 | 63 mm |
| B2 | 15 mm |
| C1 | 1 mm |
| d1 | 47 mm |
| G | M 30×1.5 |
| G1 | 32 mm |
| M | 8 mm |
| M1 | 4 mm |
| SW | 14 mm |
| r _{1,2} – min. | 1.1 mm |
| Basic dynamic load rating – C | 69.3 kN |
| Basic static load rating – C ₀ | 86.5 kN |
| Fatigue load limit – P _u | 10.8 kN |

| | |
|-----------------------------------|---|
| Maximum dynamic radial loads – Fr | 48 kN |
| Maximum static radial loads – F0r | 69.5 kN |
| Limiting speed | 1900 r/min |
| Mass support roller | 1.6 kg |
| Recommended tightening torque | 450 N·m |
| Grease fitting | NIP A3x9.5 |
| Hexagonal nut | M 30x1.5 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 1.854 |
| EAN | 7316570936209 |
| Product Group | B04144 |
| Roller Surface Profile | Flat |
| Profile | Stud Type |
| Thread Size | M30X1.5 |
| Stud Profile | Standard Stud |
| Enclosure | Sealed |
| Rolling Element | Cylindrical Roller Bearing – Double Row |
| Relubricatable | Yes |
| Hex Socket | Yes |
| Inch – Metric | Metric |
| Other Features | Full Complement Labyrinth Seal |
| Long Description | 80MM Roller Diameter; 35MM Roller Width; Flat Roller Surface; Stud Type; 30MM Stud Diameter; M30X1.5 |
| UNSPSC | 31171530 |

| | |
|--------------------------------------|----------------------------|
| Harmonized Tariff Code | 8482.50.00.00 |
| Noun | Bearing |
| Keyword String | Cam Follower |
| Manufacturer Item Number | NUKR 80 XA |
| Weight / LBS | 3.527 |
| Stud Diameter | 1.181 Inch 30 Millimeter |
| Roller Width | 1.378 Inch 35 Millimeter |
| Roller Diameter | 3.15 Inch 80 Millimeter |
| r1,2 min. | 1.1 mm |
| Basic dynamic load rating C | 69.3 kN |
| Basic static load rating C0 | 86.5 kN |
| Fatigue load limit Pu | 10.8 kN |
| Maximum dynamic radial loads Fr max. | 48 kN |
| Maximum static radial loads F0r max. | 69.5 kN |
| Mass cam follower | 1.6 kg |
| Lubrication adapter | AP 14 |