

SKF 239/1060 CAKF/W33 + OH 39/1060 H tapered roller bearings

Welcome 75 mm Shaft Size to Mounted Bearing Engineering Group the SKF 239/1060 CAKF/W33 + OH 39/1060 H tapered roller bearings online seller.

| | |
|-------------------------|--------------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 75 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | QMCW15J075SB |
| Locking Style | Eccentric |
| Weight | 22.00 lb |
| Housing Style | Piloted Flange Cartridge |
| UPC Code | 0883450062725 |
| Dimension BC | 7.50 in |
| Dimension C | 4.010 in |
| Dimension E | 5.30 in |
| Dimension B Fix | 1.81 in |
| Dimension B Exp | 1.89 in |
| Dimension F | 8.75 in |
| Dimension D | 6.38 in |
| Dimension H | 0.50 in |
| Dimension J (Bolt Size) | 0.625 in |
| Dimension M | 2.37 in |
| Dimension R | 0.06 in |
| Dimension S | 3.62 in |

| | |
|-------------------------------------|-----------|
| Dimension G | 6.375 in |
| Dimension K | 1.25 in |
| Dimension L Exp | 3.76 in |
| Dimension L Fix | 3.68 in |
| Dimension N | 1.88 in |
| C0 – Static Load | 54100 lb |
| C – Dynamic Load (Basic) | 49900 lb |
| e – Geometry Factor | 0.22 |
| Y1 – Geometry Factor | 3.14 |
| Y2 – Geometry Factor | 4.67 |
| Oil Lubrication – M/N Seal | 1600 rpm |
| Oil Lubrication – T Seal | 2900 rpm |
| Oil Lubrication – B/C/O Seal | 1300 rpm |
| Grease Lubrication – M/N Seal | 1600 rpm |
| Grease Lubrication – T Seal | 2400 rpm |
| Grease Lubrication – B/C/O Seal | 1300 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0020 in |
| Eng Internal Radial Clearance – Min | 0.0020 |
| Eng Internal Radial Clearance – Max | 0.0031 |
| Pre Install Clearance Min | 0.0020 in |
| Pre Install Clearance Max | 0.0031 in |