

SKF 24056 CCK30/W33 + A0H 24056 G tapered roller bearings

SKF 24056 CCK30/W33 + A0H 24056 G tapered roller bearings manufacturer and global supplier of 20 mm d reliable ball and roller ... SKF 24056 CCK30/W33 + A0H 24056 G tapered roller bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the 14 mm B unique requirements of our targeted industries.

d	20 mm
D	47 mm
B	14 mm
E	41.5 mm
F	26.5 mm
d1	29.7 mm
rs min	1 mm
r1s min	0.6 mm
Radial clearance class	CN
Mass (without HJ ring)	0.11 kg
Dynamic load, C	26.6 kN
Static load, C0	23.8 kN
Fatigue limit load, Cu	2.9 kN
Nref	13,000 rpm
Nlim	19,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.39 Hz

Characteristic rolling element frequency, BSF	4.31 Hz
Characteristic outer ring frequency, BPF0	4.68 Hz
Characteristic inner ring frequency, BRFI	7.32 Hz
da min	25 mm
Da max	43 mm
Db min	42 mm
Dc max	39 mm
ra max	1 mm
r1a max	0.6 mm