

SKF 24088ECAK30/W33 spherical roller bearings

SKF 24088ECAK30/W33 spherical roller bearings 88.9 mm da with easy-to-use parts graphics, giving you the ability to check parts availability, pricing, examine remanufactured options.

da	88.9 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	222.25 mm
S	4.763 mm
ba	44.45 mm
H	217.488 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
L	387.35 mm
N1	25.4 mm
R1	58.737 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	42.069 mm
Housing	SAF 520
Bearing	22220 EK
Adapter sleeve assembly	SNW 20×3.1/2

Stabilizing ring	SR-20-17
Taconite seal	TER 103
End plug (suffix Y)	EPR 12
Max. speed for Taconite seal	900 r/min
P60°	136 kN
P90°	81.4 kN
P120°	50.7 kN
P150°	46.3 kN
P180°	55.6 kN
Pa	13.8 kN
Mass pillow block	28.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.875 in
Initial grease fill	181.44 g