

# SKF 24124 CCK30/W33 + AH 24124 tapered roller bearings

Manufacturers of all are represented in our partial list of clients. 0.0 Inventory Contact Gary for a complete SKF 24124 CCK30/W33 + AH 24124 tapered roller bearings list of clients and projects.

|                      |                                   |
|----------------------|-----------------------------------|
| Inventory            | 0.0                               |
| Manufacturer Name    | TIMKEN                            |
| Minimum Buy Quantity | N/A                               |
| Weight               | 0.195                             |
| EAN                  | 0087796091627                     |
| Product Group        | B04270                            |
| Enclosure            | 2 Metal Shields                   |
| Precision Class      | ABEC 3   ISO P6                   |
| Material – Ball      | Steel                             |
| Number of Bearings   | 1 (Single)                        |
| Contact Angle        | 0 Degree                          |
| Preload              | None                              |
| Raceway Style        | Not Applicable                    |
| Cage Material        | Phenolic                          |
| Rolling Element      | Ball Bearing                      |
| Enclosure Type       | Non Contact Shield                |
| Flush Ground         | No                                |
| Inch – Metric        | Metric                            |
| Other Features       | Single Row   Deep Groove   Conrad |

|                          |  |
|--------------------------|--|
| Long Description         | 30MM Bore; 62MM Outside Diameter;<br>16MM Width; 2 Metal Shields<br>Enclosure; ABEC 3   ISO P6<br>Precision; |
| UNSPSC                   | 31171504   |
| Harmonized Tariff Code   | 8482.10.50.68  |
| Noun                     | Bearing  |
| Keyword String           | Deep Groove Ball   |
| Manufacturer Item Number | M206KDD A3158A   |
| Weight / LBS             | 0.43   |
| D                        | 2.441 Inch   62 Millimeter   |
| d                        | 1.181 Inch   30 Millimeter   |
| B                        | 0.63 Inch   16 Millimeter  |