

SKF 30220J2/DF tapered roller bearings

Browse SKF 30220J2/DF tapered roller bearings Categories in the Manufacturers Online Free. including 90x60x44 Size (mm) .

Size (mm)	90x60x44
Bore Diameter (mm)	90
Outer Diameter (mm)	60
Width (mm)	44
d	60 mm
D	90 mm
B	44 mm
C	36 mm
α	6 °
dk	80 mm
r1 – min.	1 mm
r2 – min.	1 mm
da – min.	66.5 mm
da – max.	66.8 mm
Da – min.	80 mm
Da – max.	84 mm
ra – max.	1 mm
rb – max.	1 mm
Basic dynamic load rating – C	695 kN
Basic static load rating – C0	1160 kN

Specific factor dinamic load – K	300 N/mm2
Specific factor static load – K0	500 N/mm2
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.1
EAN	7316571875507
Product Group	B04264
Self Aligning	Yes
Rolling Element	Spherical Plain
Material – Outer Member	Steel
Material – Ball	Steel
Material – Liner	Teflon
Relubricatable	No
Enclosure	2 Seals
Other Features	2 Piece Maintenance Free Chrome Plated Ball Self Lubricating Triple Lip Heavy Duty Seals
Long Description	60MM Bore; 36MM Housing Width; 90MM Outside Diameter; Spherical Plain; Steel Outer Member; Steel Bal
Inch – Metric	Metric
UNSPSC	31171515
Harmonized Tariff Code	8483.30.80.70
Noun	Bearing
Keyword 3	Spherical
Keyword String	Plain Spherical Radial

Manufacturer Item Number	GE 60 TXE-2LS
Weight / LBS	2.425
Outside Diameter	3.543 Inch 90 Millimeter
Bore	2.362 Inch 60 Millimeter
Overall Width	1.732 Inch 44 Millimeter
Housing Width	1.417 Inch 36 Millimeter
bore diameter:	60 mm
outer ring width:	36 mm
outside diameter:	90 mm
grade:	Commercial/Industrial
misalignment angle:	6 °
race material:	PTFE Composite
inner ring width:	44 mm
overall width:	44 mm
bearing type:	Radial
radial static load capacity:	1160 kN
lubrication type:	Maintenance Free/Self-Lubricating
radial dynamic load capacity:	695 kN
closure type:	Triple Lip Seals
operating temperature range:	-50 to +150 °C °F
outer ring material:	Chrome Steel
manufacturer upc number:	7316571875507
inner ring material:	Chrome Steel
Lubricant	Maintenance free – dry lubrication
Design (sliding contact surface combination)	Steel/PTFE fabric
Sealing solution	Triple-lip seals

α	6 °
r1 min.	1 mm
r2 min.	1 mm
da min.	66.5 mm
da max.	66.8 mm
Da min.	80 mm
Da max.	84 mm
ra max.	1 mm
rb max.	1 mm
Basic dynamic load rating C	695 kN
Basic static load rating C0	1160 kN
Specific dynamic load factor K	300 N/mm ²
Specific static load factor K0	500 N/mm ²
Mass plain bearing	1 kg