

# SKF 30352 J2 tapered roller bearings

offers a SKF 30352 J2 tapered roller bearings selection of Genuine at Wholesale Prices. We are a SKF 30352 J2 tapered roller bearings Certified Parts 150 mm Da Retailer 71.438 mm da

da	71.438 mm
Da	150 mm
Ca	45.796 mm
A1	88.9 mm
A2	127 mm
S	4.763 mm
ba	35.719 mm
H	187.325 mm
H1	95.25 mm
H2	38.1 mm
J min.	250.825 mm
J max.	279.4 mm
L	330.2 mm
N1	23.813 mm
R1	53.975 mm
R2	22.225 mm
RG	3/8 NPT
PG	1/8 NPT
h	34.925 mm
Housing	SAFS 517
Bearing	22217 EK

Adapter sleeve assembly	SNW 17×2.13/16
Stabilizing ring	SR-17-14
Labyrinth ring	2 x LOR 51
PosiTrac Plus contact element	2 x B10724-53
End plug (suffix Y)	EPR 9
Max. speed for PosiTrac Plus seal	1950 r/min
P60°	78.7 kN
P90°	47.2 kN
P120°	28.9 kN
P150°	26.7 kN
P180°	32 kN
Pa	9.25 kN
Mass pillow block	24.5 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	110.56 g