

SKF 331933/Q tapered roller bearings

are N/A Minimum Buy Quantity a few brands 0.0 Inventory you will find in our inventory. Find SKF 331933/Q tapered roller bearings to see what's in stock!

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	9.53
EAN	7316576675034
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Concentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	22215
Seals	Garter Spring
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Double Row Heavy Duty Open End With Set Screw
Long Description	2 Bolt Pillow Block; 3" Bore; 3-1/4" Base to Center Height; Concentric Collar Mount; Spher

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SYR 3-3
Weight / LBS	21
B	92.075 mm
Bolt Spacing Minimum	7.813 Inch 198.44Millimeter
Nominal Bolt Center to Center	8.1 Inch 206.4 Millimeter
d	3 Inch 76.2 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
D	3.625 Inch 92.075 Millimeter
Bolt Spacing Maximum	8.438 Inch 214.325Millimeter
bore diameter:	3.0000 in
bolt center-to-center length:	206.375 mm
overall length:	10.4375 in
base width:	65.1 mm
overall height:	6.4375 in
expansion type:	Expansion Bearing (Floating)
mounting:	Two-Bolt Base
finish/coating:	Uncoated
bearing type:	Spherical Roller
overall width:	3-5/8 in
bore type:	Round
seal type:	Contact/Lip
housing construction:	Solid Pillow Block
radial dynamic load capacity:	158 kN
base to bore centerline:	3.2500 in
radial static load capacity:	208 kN

duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	SYR
locking device:	Set Screw
replacement bearing:	22215
da	76.2 mm
d2	111.125 mm
A	68.263 mm
A1	95.25 mm
H	165.894 mm
H1	82.55 mm
H2	57.15 mm
L	265.113 mm
J max.	223.838 mm
J min.	198.438 mm
s	31.75 mm
S	0.794 mm
Basic dynamic load rating C	158 kN
Limiting speed	950 r/min
Mass bearing unit	9.53 kg
Attachment bolt diameter G	19.05 mm