

# SKF 332168 tapered roller bearings

SKF 332168 tapered roller bearings Product Brochures , Manufacturing Service . Get 0.0 Inventory Your Free.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 17.706   |
| EAN                       | 0883450111355  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | V Lock   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 7/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22219  |
| Seals                     | Teflon Labyrinth   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Nut  |
| Long Description          | 2 Bolt Pillow Block; 3-7/16" Bore; 3-3/4" Base to Center Height; V Lock Mount; Spherical R |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | QVP19V307ST                    |
| Weight / LBS                  | 39                             |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| d                             | 3.438 Inch   87.325 Millimeter |
| D                             | 3.69 Inch   93.726 Millimeter  |
| Bolt Spacing Minimum          | 9.375 Inch   238.125Millimeter |
| B                             | 3.75 Inch   95.25 Millimeter   |
| Bolt Spacing Maximum          | 11.25 Inch   285.75Millimeter  |
| Nominal Bolt Center to Center | 10.3 Inch   260.5 Millimeter   |