

SKF 51238M thrust ball bearings

What are the types of SKF 51238M thrust ball bearings 55 mm d 120 mm D ? Manufacturing Service . Get Your Free, Instant price, design review.

d	55 mm
D	120 mm
B	29 mm
E	104.5 mm
F	70.5 mm
d1	77.2 mm
rs min	2 mm
r1s min	2 mm
Radial clearance class	C3
Mass (without HJ ring)	1.52 kg
Dynamic load, C	111 kN
Static load, C0	111 kN
Fatigue limit load, Cu	13.5 kN
Nlim (oil)	7,000 rpm
Nlim (grease)	5,900 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	64 mm
Da max	111 mm
Db min	106 mm

Dc max	103 mm
ra max	2 mm
r1a max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.5
EAN	4547359151565
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Outer Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	2 Rib Inner Ring Plain Outer Ring Cage on Inner Ring OD
Long Description	55MM Bore; Straight Bore Profile; 120MM Outside Diameter; 29MM Width; Brass Cage Material; RBEC 1
UNSPSC	31171547

Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	N311G1C3
Weight / LBS	3.297
Bore	2.165 Inch 55 Millimeter
Width	1.142 Inch 29 Millimeter
Outside Diameter	4.724 Inch 120 Millimeter