

# SKF 6203-Z deep groove ball bearings

SKF 6203-Z deep groove ball bearings SKF Manufacturer Name Manufacturers , Online Wholesale Suppliers N/A Minimum Buy Quantity ! 0.0 Inventory

|                      |  |
|----------------------|--|
| Inventory            | 0.0  |
| Manufacturer Name    | SKF  |
| Minimum Buy Quantity | N/A  |
| Weight               | 2.072  |
| EAN                  | 7316577127938  |
| Product Group        | B04270   |
| Enclosure            | Open   |
| Precision Class      | ABEC 7   ISO P4  |
| Material – Ball      | Steel  |
| Number of Bearings   | 2 (1 Pair)   |
| Contact Angle        | 25 Degree  |
| Preload              | Light  |
| Raceway Style        | 1 Rib Outer Ring   |
| Cage Material        | Phenolic   |
| Rolling Element      | Ball Bearing   |
| Mounting Arrangement | Duplex-Universal   |
| Flush Ground         | Yes  |
| Inch – Metric        | Metric   |
| Other Features       | Single Row   Angular Contact   Super Precision   High Capacity |

|                               |  |
|-------------------------------|--|
| Long Description              | 65MM Bore; 120MM Outside Diameter; 46MM Width; Open Enclosure; ABEC 7   ISO P4 Precision; Steel Ball |
| UNSPSC                        | 31171531   |
| Harmonized Tariff Code        | 8482.10.50.28  |
| Noun                          | Bearing  |
| Keyword String                | Angular Contact Ball   |
| Manufacturer Item Number      | 7213 ACD/P4ADGA  |
| Weight / LBS                  | 4.564  |
| B                             | 1.811 Inch   46 Millimeter   |
| d                             | 2.559 Inch   65 Millimeter   |
| D                             | 4.724 Inch   120 Millimeter  |
| bore diameter:                | 65 mm  |
| radial dynamic load capacity: | 72.8 kN  |
| outside diameter:             | 120 mm   |
| radial static load capacity:  | 57 kN  |
| overall width:                | 23 mm  |
| outer ring width:             | 23 mm  |
| contact angle:                | 25 °   |
| maximum rpm:                  | 17000 RPM  |
| row type & fill slot:         | Single-Row Non-Fill Slot   |
| finish/coating:               | Uncoated   |
| internal clearance:           | C0   |
| precision rating:             | ABEC 7 (ISO Class 4)   |
| closure type:                 | Open   |
| fillet radius:                | 1.5 mm   |
| bearing material:             | Steel  |
| series:                       | 72   |