

SKF 6310-ZNR deep groove ball bearings

SKF 6310-ZNR deep groove ball bearings Deal 40 Outer Diameter (mm) is your source 22x40x58 Size (mm) 22 Bore Diameter (mm) for OEM and accessories. We sell Genuine at discount prices.

Size (mm)	22x40x58
Bore Diameter (mm)	22
Outer Diameter (mm)	40
Width (mm)	58
D	40 mm
d	22 mm
B	58 mm
C	20 mm
B1	36.5 mm
B2	8 mm
B3	16 mm
C1	0.8 mm
d1	31.5 mm
G	M 18×1.5
G1	19 mm
M	6 mm
M1	3 mm
SW	8 mm
c	1 mm
r1,2 – min.	1 mm
Basic dynamic load rating – C	10.5 kN
Basic static load rating – C0	14.6 kN

Fatigue load limit – Pu	1.7 kN
Maximum dynamic radial loads – Fr	12.5 kN
Maximum static radial loads – F0r	18 kN
Limiting speed	3400 r/min
Mass support roller	0.255 kg
Recommended tightening torque	87 N·m
Grease fitting	NIP A2x7.5
Hexagonal nut	M 18x1.5
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.26
EAN	7316571594880
Product Group	B04144
Roller Surface Profile	Crowned
Profile	Stud Type
Thread Size	M18X1.5
Stud Profile	Standard Stud with Eccentric Bushing
Enclosure	Sealed
Rolling Element	Needle Bearing
Relubricatable	Yes
Hex Socket	Yes
Inch – Metric	Metric
Other Features	Caged Polyamide 66 Axial Sliding 3 Stage Sealing
Long Description	40MM Roller Diameter; 20MM Roller Width; Crowned Roller Surface; Stud Type; 18MM Stud Diameter; M18X

UNSPSC	31171530
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Cam Follower
Manufacturer Item Number	KRE 40 PPA
Weight / LBS	0.573
Stud Diameter	0.709 Inch 18 Millimeter
Roller Diameter	1.575 Inch 40 Millimeter
Roller Width	0.787 Inch 20 Millimeter
r _{1,2} min.	1 mm
Basic dynamic load rating C	10.5 kN
Basic static load rating C ₀	14.6 kN
Fatigue load limit P _u	1.73 kN
Maximum dynamic radial loads F _r max.	12.5 kN
Maximum static radial loads F _{0r} max.	18 kN
Mass cam follower	0.26 kg
Lubrication adapter	AP 8