

SKF 6320 M deep groove ball bearings

Manufacturers of 62 Outer Diameter (mm) all are represented in our partial list of clients. Contact Gary for a complete SKF 6320 M deep groove ball bearings 25 Bore Diameter (mm) list of clients and 25x62x24 Size (mm) projects.

| | |
|-------------------------------|--------------|
| Size (mm) | 25x62x24 |
| Bore Diameter (mm) | 25 |
| Outer Diameter (mm) | 62 |
| Width (mm) | 24 |
| d | 25 mm |
| D | 62 mm |
| B | 24 mm |
| C | 24 mm |
| r min. | 1,1 mm |
| da min. | 31,5 mm |
| Da max. | 55,5 mm |
| ra max. | 1 mm |
| Weight | 0,319 Kg |
| Basic dynamic load rating (C) | 24,9 kN |
| Basic static load rating (C0) | 6,6 kN |
| (Grease) Lubrication Speed | 9 500 r/min |
| (Oil) Lubrication Speed | 12 000 r/min |
| Calculation factor (e) | 0,47 |
| Calculation factor (Y0) | 1,4 |
| Calculation factor (Y1) | 1,4 |
| rs min | 1.1 mm |

| | |
|---------------------------------|------------|
| Associated sleeve reference | H2305X |
| e | 0.47 |
| Y1 | 1.4 |
| Y2 | 2.1 |
| Y0 | 1.4 |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 0.32 kg |
| Dynamic load, C | 24.9 kN |
| Static load, C0 | 6.6 kN |
| Nlim (oil) | 12,000 rpm |
| Nlim (grease) | 9,500 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| da min | 31.5 mm |
| da max | 34 mm |
| db min | 29 mm |
| Ce min | 5 mm |
| Da max | 55.5 mm |
| ra max | 1 mm |