

SKF 7006 ACB/P4A angular contact ball bearings

Enjoy High Margins on Competitive 15 mm d Pricing.Great Wholesale Products at Low Costs.

d	15 mm
D	32 mm
B	9 mm
d1	20.9 mm
d2	19.7 mm
D1	26.1 mm
D2	28.6 mm
a	10 mm
Contact angle α	25 °
rs min	0.3 mm
rls min	0.15 mm
f0	14.4
Precision class	P42
Mass	0.03 kg
Dynamic load, C	6.35 kN
Static load, C0	3.55 kN
Nlim (oil)	69,800 rpm
Nlim (grease)	43,200 rpm
Preload level	GL
Preload value	0.02 kN
Axial rigidity	38.7 N/ μ m
Radial rigidity	85 N/ μ m
Min operating temperature, Tmin	-20 °C

Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	4.77 Hz
Characteristic outer ring frequency, BPF0	4.9 Hz
Characteristic inner ring frequency, BRFI	7.1 Hz
da min	17.5 mm
Da max	29.5 mm
Db max	30.8 mm
r1a max	0.15 mm
ra max	0.3 mm
D6	21.3 mm