

# SKF 7006 CD/HCP4AH angular contact ball bearings

What are the types of SKF 7006 CD/HCP4AH angular contact ball bearings 61,913 Outer Diameter (mm) ? Manufacturing Service . Get Your Free, Instant price, design 60×61.913×43 Size (mm) review.

Size (mm)	60×61.913×43
Bore Diameter (mm)	60
Outer Diameter (mm)	61,913
Width (mm)	43
d	61.913 mm
A	60 mm
A1	43 mm
H	29.5 mm
H1	69.9 mm
H2	26.5 mm
L	240 mm
J	190.5 mm
N1	18 mm
B	65.1 mm
s1	39.7 mm
Basic dynamic load rating – C	52.7 kN
Basic static load rating – C0	36 kN
Limiting speed	100 r/min
Limiting temperature – T	350 °C
Mass bearing unit	4.5 kg

Grub (set) screw – G2 – 3/8-24 UNF	3/824 UNF
Hexagonal key size for grub screw – H	4.762 mm
Recommended tightening torque for grub screw	16.5 N·m
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	4.656
EAN	7316571381176
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	YAR 212-207-2F/VA228
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Inch
Other Features	Single Row   Standard Duty   Wide Inner Race   High Temperature Bearing with Graphite   Has Flinger

Long Description	2 Bolt Pillow Block; 2-7/16" Bore; 2-3/4" Base to Center Height; Set Screw Mount; Ball Bea
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SY 2.7/16 TF/VA228
Weight / LBS	11
Bore	2.438 Inch   61.925 Millimeter
Nominal Bolt Center to Center	7.3 Inch   184 Millimeter
Base to Center Height	2.75 Inch   69.85 Millimeter
Bolt Spacing Maximum	7.938 Inch   201.625Millimeter
Bolt Spacing Minimum	7.063 Inch   179.4Millimeter
Length Thru Bore	2.563 Inch   65.09 Millimeter
Actual Bolt Center to Center	0 Inch   0Millimeter
mounting:	Two-Bolt Base
overall width:	42 mm
bore diameter:	2.4375 in
radial dynamic load capacity:	11860 lbf
bore type:	Round
radial static load capacity:	8100 lbf
base to bore centerline:	2.7520 in
base width:	60 mm
housing material:	Cast Iron
bolt center-to-center length:	190.5 mm

locking device:	Set Screw
maximum rpm:	3400 RPM
expansion type:	Non-Expansion Bearing (Fixed)
lubrication type:	Lubrication Fitting
overall length:	240 mm
series:	SY
overall height:	139.5 mm
replacement bearing:	YAR 212-207-2F
finish/coating:	Uncoated
standards met:	ISO
N	29.5 mm
Basic dynamic load rating C	52.7 kN
Basic static load rating C0	36 kN
Limiting temperature T max.	350 °C
Grub (set) screw G2	3/8-24 UNF
Hexagonal key size for grub screw N	4.763 mm
Attachment bolts, recommended metric size G	16 mm
Bearing	YAR 212-207-2FW/VA228