

SKF 7010 ACE/HCP4AH1 angular contact ball bearings

SKF 7010 ACE/HCP4AH1 angular contact ball bearings SKF Manufacturer Name Engineering Calculator , 0.0 Inventory Manufacturing Service . Get Your Free.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	24.061
EAN	7316576668623
Product Group	M06288
Number of Mounting Holes	2
Mounting Method	Shaft Mount
Housing Style	2 Bolt Pillow Block
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Insert Part Number	22315 CC/W33
Seals	Labyrinth
Housing Configuration	2 Piece Split
Inch – Metric	Metric
Other Features	Double Row Heavy Duty
Long Description	2 Bolt Pillow Block; 75MM Bore; 101.6MM Base to Center Height; Shaft Mount Mount; Spherical Roller B

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SAF 22315
Weight / LBS	48
B	4 Inch 101.6 Millimeter
Nominal Bolt Center to Center	11 Inch 280 Millimeter
D	5.875 Inch 149.225 Millimeter
Actual Bolt Center to Center	0 Inch 0Millimeter
Bolt Spacing Minimum	10.375 Inch 263.525Millimeter
Bolt Spacing Maximum	11.625 Inch 295.275Millimeter
d	2.953 Inch 75 Millimeter
da	75 mm
db	87.325 mm
dc	71.425 mm
Da	160 mm
Ca	64.795 mm
A1	98.425 mm
A2	149.225 mm
S	4.763 mm
ba	44.45 mm
H	192.088 mm
H1	101.6 mm
H2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
L	349.25 mm

N1	22.225 mm
R1	60.325 mm
R2	27.94 mm
RG	3/8 NPT
PG	1/8 NPT
h	40.481 mm
Housing	SAF 315
Bearing	22315 E
Lock nut	AN 15
Lock washer	W 15
Stabilizing ring	SR-18-15
Labyrinth ring (db shaft position)	LOR 79
Labyrinth ring (dc shaft position)	LOR 46
End plug (suffix Y)	EPR 8
Bearing limiting speed	4300 r/min
P60°	121 kN
P90°	72.5 kN
P120°	45.4 kN
P150°	40.5 kN
P180°	49.8 kN
Pa	32 kN
Mass pillow block	24 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in

Initial grease fill	141.75 g
---------------------	----------