

# SKF 7022 CD/P4AL angular contact ball bearings

SKF 7022 CD/P4AL angular contact ball bearings Product Brochures , 19283 Cup Part Number Manufacturing 19000 Series Service . Get Your Free.

|   |               |
|---|---------------|
| Series  | 19000         |
| Cone Part Number  | 19149X        |
| Cup Part Number   | 19283         |
| Design Units  | Imperial      |
| Bearing Weight  | 0.30 Kg       |
| Cage Type   | Stamped Steel |
| d   | 38.001 mm     |
| D   | 71.999 mm     |
| B – Cone Width  | 16.520 mm     |
| C – Cup Width   | 14.288 mm     |
| B   | 17.021 mm     |
| R – Cone Backface To Clear Radius <sup>1</sup>                    | 2.030 mm      |
| r – Cup Backface To Clear Radius <sup>2</sup>                     | 1.52 mm       |
| da – Cone Frontface Backing Diameter                              | 42.93 mm      |
| db – Cone Backface Backing Diameter                               | 45.97 mm      |
| Da – Cup Frontface Backing Diameter                               | 66.50 mm      |
| Db – Cup Backface Backing Diameter                                | 62.99 mm      |
| Ab – Cage-Cone Frontface Clearance                                | 2.3 mm        |
| Aa – Cage-Cone Backface Clearance                                 | 0.8 mm        |
| a – Effective Center Location <sup>3</sup>                        | -1.5 mm       |
| C90 – Dynamic Radial Rating (90 million revolutions) <sup>4</sup> | 2960 lbf      |

|  |           |
|--|-----------|
| C1 – Dynamic Radial Rating (1 million revolutions) <sup>5</sup>    | 11400 lbf |
| C0 – Static Radial Rating  | 13000 lbf |
| Ca90 – Dynamic Thrust Rating (90 million revolutions) <sup>6</sup> | 2250 lbf  |
| K – Factor <sup>7</sup>  | 1.31      |
| e – ISO Factor <sup>8</sup>  | 0.44      |
| Y – ISO Factor <sup>9</sup>  | 1.35      |
| G1 – Heat Generation Factor (Roller-Raceway)                       | 17.5      |
| G2 – Heat Generation Factor (Rib-Roller End)                       | 11.5      |
| Cg – Geometry Factor   | 0.0694    |