

# SKF 7040 BGM angular contact ball bearings

Offer High Quality Brand SKF 7040 BGM angular contact ball bearings .Contact Us 0.0 Inventory Online to Get Best Quote.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 19.522   |
| EAN                       | 0883450012607  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22218  |
| Seals                     | Double Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Double Collar  <br>With Set Screw   |
| Long Description          | 4 Bolt Pillow Block; 3-1/2"<br>Bore; 4" Base to Center Height;<br>Concentric Collar Mount; Spher |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | QAAPX18A308SEC                 |
| Weight / LBS                  | 64                             |
| B                             | 4 Inch   101.6 Millimeter      |
| D                             | 5.18 Inch   131.572 Millimeter |
| Bolt Spacing Minimum          | 10.81 Inch   274.574Millimeter |
| Nominal Bolt Center to Center | 11.5 Inch   292.1 Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| d                             | 3.5 Inch   88.9 Millimeter     |
| Bolt Spacing Maximum          | 12.19 Inch   309.626Millimeter |