

SKF 71900 CE/HCP4AH angular contact ball bearings

SKF 71900 CE/HCP4AH angular contact ball bearings
Manufacturers 11x5x3 Size (mm) , 5 Outer Diameter (mm) Online
Wholesale Suppliers !

Size (mm)	11x5x3
Bore Diameter (mm)	11
Outer Diameter (mm)	5
Width (mm)	3
d	5 mm
D	11 mm
B	3 mm
d1	6.81 mm
D1	9.19 mm
r1,2 – min.	0.15 mm
da – min.	5.8 mm
Da – max.	10.2 mm
ra – max.	0.1 mm
Basic dynamic load rating – C	0.468 kN
Basic static load rating – C0	0.143 kN
Fatigue load limit – Pu	0.006 kN
Reference speed	120000 r/min
Limiting speed	75000 r/min
Calculation factor – kr	0.015
Calculation factor – f0	7.1
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	0.004
EAN	7316577121585
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	5MM Bore; 11MM Outside Diameter; 3MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Fi
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	618/5
Weight / LBS	0.01
Bore	0.197 Inch 5 Millimeter
Outer Race Width	0.118 Inch 3 Millimeter
Outside Diameter	0.433 Inch 11 Millimeter
bore diameter:	5 mm
static load capacity:	0.143 kN
outside diameter:	11 mm
precision rating:	Not Rated

overall width:	3 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	3 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.1 mm
snap ring included:	Without Snap Ring
maximum rpm:	75000 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	0.468 kN
d1 ≈	6.81 mm
D1 ≈	9.19 mm
r1,2 min.	0.15 mm
da min.	5.8 mm
Da max.	10.2 mm
ra max.	0.1 mm
Basic dynamic load rating C	0.468 kN
Basic static load rating C0	0.143 kN
Fatigue load limit Pu	0.006 kN
Calculation factor kr	0.015
Calculation factor f0	7.1
Mass bearing	0.0012 kg