SKF ALS7ABP/232298 angular contact ball bearings

Advance SKF ALS7ABP/232298 angular contact ball bearings is your source for quality and accessories. Mounted Bearing Engineering Group shop Imperial Shaft Size Type online for home delivery or pick up in one of our 10000.

| Engineering Group | Mounted Bearing |
|--------------------------|-------------------------|
| Shaft Size | 3-1/2 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | QVVFX19V308SB |
| Locking Style | Double V-Lock |
| Weight | 35 lb |
| Housing Style | Four-Bolt Square Flange |
| UPC Code | 0883450367752 |
| Dimension BC | 9.5 in |
| Dimension C | 4.9 in |
| Dimension D | 7.630 in |
| Dimension E | 6.72 in |
| Dimension F | 8.37 in |
| Dimension H | 1.31 in |
| Dimension J (Bolt Size) | 0.75 in |
| Dimension L Exp | 3.96 in |
| Dimension L Fix | 3.87 in |
| Dimension N | 3.310 in |
| Dimension RVV | 0.62 in |
| Dimension SVV | 4.49 in |
| C — Dynamic Load (Basic) | 86600 lb |

| CO — Static Load | 99000 lb |
|-------------------------------------|-----------|
| e — Geometry Factor | 0.24 |
| Y1 - Geometry Factor | 2.80 |
| Y2 - Geometry Factor | 4.17 |
| Oil Lubrication — M/N Seal | 1300 rpm |
| Oil Lubrication — T Seal | 2200 rpm |
| Oil Lubrication — B/C/O Seal | 1000 rpm |
| Grease Lubrication — M/N Seal | 1300 rpm |
| Grease Lubrication — T Seal | 1800 rpm |
| Grease Lubrication — B/C/O Seal | 950 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0030 in |
| Eng Internal Radial Clearance — Min | 0.0043 |
| Eng Internal Radial Clearance — Max | 0.0055 |
| Pre Install Clearance Min | 0.0043 in |
| Pre Install Clearance Max | 0.0055 in |