

SKF BB1B630842B deep groove ball bearings

170 Million used SKF BB1B630842B deep groove ball bearings instantly searchable. Shop our large selection of parts based on brand, price, description, 290x190x75 Size (mm) 290 Bore Diameter (mm) and location. Order the with stock ...

Size (mm)	290x190x75
Bore Diameter (mm)	290
Outer Diameter (mm)	190
Width (mm)	75
d	190 mm
D	290 mm
B	75 mm
d2	216 mm
D1	261 mm
b	13.9 mm
K	7.5 mm
r1,2 – min.	2.1 mm
da – min.	197 mm
da – max.	216 mm
Da – max.	279 mm
ra – max.	2 mm
Basic dynamic load rating – C	916 kN
Basic static load rating – C0	1340 kN
Fatigue load limit – Pu	122 kN
Reference speed	1900 r/min
Limiting speed	2400 r/min

Calculation factor – e	0.23
Calculation factor – Y1	2.9
Calculation factor – Y2	4.4
Calculation factor – Y0	2.8
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	17.099
EAN	7316576601705
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH3038 (Specify bore)
Withdrawal Nut	HML41T
Inch – Metric	Metric
Long Description	190MM Tapered Bore; 290MM Outside Diameter; 75MM Width; C0-Medium Clearance; Adapter Mount; Double R
Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
UNSPSC	31171510
Harmonized Tariff Code	84823080

Noun	Bearing
Keyword String	Spherical
Weight / LBS	37.664
Width	2.953 Inch 75 Millimeter
Outside Diameter	11.417 Inch 290 Millimeter
Adapter Part Number	SNW3038 H3038 HE3038 (Specify Bore) Inch H3038 (Specify bore) Millimeter
Bore	7.48 Inch 190 Millimeter
d2 ≈	216 mm
D1 ≈	261 mm
r1,2 min.	2.1 mm
Da max.	279 mm
ra max.	2 mm
Basic dynamic load rating C	916 kN
Basic static load rating C0	1340 kN
Fatigue load limit Pu	122 kN
Calculation factor e	0.23
Calculation factor Y1	2.9
Calculation factor Y2	4.4
Calculation factor Y0	2.8
Mass bearing	17.4 kg