

# SKF BK0709 needle roller bearings

LET OUR SKF BK0709 needle roller bearings EXPERTS GET REXNORD Manufacturer Name YOU THE PARTS YOU 0.0 Inventory NEED.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 12.167  |
| EAN                       | 0793699902655   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Tapered Adapter Sleeve  |
| Housing Style             | 4 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 5/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 6215U   |
| Seals                     | Light Contact   |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Double Row  |
| Long Description          | 4 Bolt Pillow Block; 2-15/16" Bore; 3-1/4" Base to Center Height; Tapered Adapter Sleeve<br>M |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | KAS6215F                       |
| Manufacturer Internal Number  | 190265                         |
| Weight / LBS                  | 26.8                           |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter           |
| B                             | 3.25 Inch   82.55 Millimeter   |
| D                             | 4.531 Inch   115.09 Millimeter |
| Nominal Bolt Center to Center | 8.1 Inch   206.4 Millimeter    |
| d                             | 2.938 Inch   74.625 Millimeter |
| Actual Bolt Center to Center  | 8.1 Inch   206Millimeter       |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter           |