

SKF C 30/600 KM + AOHX 30/600 cylindrical roller bearings

Various types and sizes to accommodate your Mounted Bearing Engineering Group SKF C 30/600 KM + AOHX 30/600 cylindrical roller bearings requirements. Imperial Shaft Size Type

Engineering Group	Mounted Bearing
Shaft Size	4 in
Shaft Size Type	Imperial
Full Timken Part Number	99999B
Locking Style	Single V-Lock
Weight	55 lb
Housing Style	Four-Bolt Square Flange
UPC Code	0883450042994
Dimension BC	12.2 in
Dimension C	5.5 in
Dimension D	9.040 in
Dimension E	7.60 in
Dimension F	9.500 in
Dimension H	1.50 in
Dimension J (Bolt Size)	1 in
Dimension G	1.75 in
Dimension L	4.41 in
Dimension N	4.120 in
Dimension RV	0.47 in
Dimension SV	4.13 in
C0 – Static Load	147000 lb
C – Dynamic Load (Basic)	125000 lb

e – Geometry Factor	0.26
Y1 – Geometry Factor	2.55
Y2 – Geometry Factor	3.80
Oil Lubrication – M/N Seal	900 rpm
Oil Lubrication – T Seal	1700 rpm
Oil Lubrication – B/C/O Seal	600 rpm
Grease Lubrication – M/N Seal	900 rpm
Grease Lubrication – T Seal	1200 rpm
Grease Lubrication – B/C/O Seal	600 rpm
Float	0.083 in
Shaft Tolerance	0.0030 in
Eng Internal Radial Clearance – Min	0.0053
Eng Internal Radial Clearance – Max	0.0067
Pre Install Clearance Min	0.0043 in
Pre Install Clearance Max	0.0055 in