

SKF C 39/1180 KMB cylindrical roller bearings

LET 77.787 mm db 61.913 mm dc OUR SKF C 39/1180 KMB cylindrical roller bearings 65 mm da EXPERTS GET YOU THE PARTS YOU NEED.

da	65 mm
db	77.787 mm
dc	61.913 mm
Da	120 mm
Ca	39.014 mm
A1	79.375 mm
A2	112.713 mm
S	3.969 mm
ba	31.75 mm
H	147.637 mm
H1	76.2 mm
H2	25.4 mm
J min.	206.375 mm
J max.	241.3 mm
L	279.4 mm
N1	19.05 mm
R1	44.45 mm
R2	15.875 mm
RG	1/8 NPT
PG	1/8 NPT
h	27.781 mm
Housing	SAF 213

Bearing	22213 E
Lock nut	N 13
Lock washer	W 13
Stabilizing ring	SR-13-0
Labyrinth ring (db shaft position)	LOR 55
Labyrinth ring (dc shaft position)	LOR 37
End plug (suffix Y)	EPR 7
Bearing limiting speed	7000 r/min
P60°	50.3 kN
P90°	30.2 kN
P120°	18 kN
P150°	16 kN
P180°	19.1 kN
Pa	12 kN
Mass pillow block	9.98 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	81.3 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	53.865 g