

# SKF C4010K30TN9 cylindrical roller bearings

High Quality SKF C4010K30TN9 cylindrical roller bearings. Competitive Pricing. Accept Small Order. Easy 160x75x37 Size (mm) and Fast Shipping. 75 Outer Diameter (mm)

Size (mm)	160x75x37
Bore Diameter (mm)	160
Outer Diameter (mm)	75
Width (mm)	37
d	75 mm
D	160 mm
B	37 mm
d1	104 mm
D1	135.75 mm
F	95 mm
r1,2 – min.	2.1 mm
r3,4 – min.	2.1 mm
s	1.8 mm
da – min.	87 mm
da – max.	92 mm
db – min.	107 mm
Da – max.	148 mm
ra – max.	2 mm
Basic dynamic load rating – C	280 kN
Basic static load rating – C0	265 kN
Fatigue load limit – Pu	33.5 kN
Reference speed	4500 r/min

Limiting speed	8000 r/min
Calculation factor – kr	0.23
d1 ≈	104 mm
D1 ≈	135.75 mm
r1,2 min.	2.1 mm
r3,4 min.	2.1 mm
s max.	1.8 mm
da min.	87 mm
da max.	92 mm
db min.	107 mm
Da max.	148 mm
ra max.	2 mm
Basic dynamic load rating C	280 kN
Basic static load rating C0	265 kN
Fatigue load limit Pu	33.5 kN
Calculation factor kr	0.23
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	3.79 kg
Angle ring	HJ 315 EC