

# SKF E2.3310A-2Z angular contact ball bearings

YOU'LL 20x90x47 Size (mm) FIND AN EXTENSIVE SELECTION 20 Bore Diameter (mm) OF SKF E2.3310A-2Z angular contact ball bearings FOR SALE.

Size (mm)	20x90x47
Bore Diameter (mm)	20
Outer Diameter (mm)	90
Width (mm)	47
d	20 mm
H	90 mm
A	47 mm
A1	44.26 mm
A2	32 mm
A3	13 mm
d1	26 mm
D1	64 mm
D2	60 mm
D3	36 mm
Basic dynamic load rating – C	22 kN
Basic static load rating – C0	49 kN
Fatigue load limit – Pu	1.8 kN
Limiting speed, Preload class A	7600 r/min
Limiting speed for oil lubrication	3800 mm/min
Preload class A	1480 N
Preload class B	2960 N
Frictional moment, Preload class A	0.05 N·m

Frictional moment, Preload class B	0.091 N·m
Static Axial rigidity, Preload class A	680 N/micron
Static Axial rigidity, Preload class B	860 N/micron
Basic dynamic load rating C	22 kN
Basic static load rating C0	49 kN
Fatigue load limit Pu	1.8 kN
Attainable speed for preload class A	7600 r/min
Attainable speed for preload class B	3800 r/min
Frictional moment for preload class A	0.05 N·m
Frictional moment for preload class B	0.091 N·m
Static axial stiffnes for preload class A	680 N/μm
Static axial stiffnes for preload class B	860 N/μm
Mass cartridge unit	1.1 kg
Through hole diameter for attachment bolts N	6.6 mm
Pitch diameter of attachment bolt holes J	76 mm
Cartridge half diameter without flange J1	32 mm