

# SKF FBSA 212 A/QBC thrust ball bearings

YOU'LL 0.0 Inventory FIND AN EXTENSIVE SELECTION OF SKF FBSA 212 A/QBC thrust ball bearings SKF Manufacturer Name FOR SALE.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | SKF  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 8.088  |
| EAN                       | 7316577315069  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Tapered Adapter Sleeve   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 1211 EK  |
| Seals                     | Labyrinth  |
| Housing Configuration     | 2 Piece Split  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Medium Duty   |
| Long Description          | 2 Bolt Pillow Block; 1-15/16" Bore; 2-3/4" Base to Center Height; Tapered Adapter Sleeve M |
| UNSPSC                    | 31171511   |

|                               |                                |
|-------------------------------|--------------------------------|
| Harmonized Tariff Code        | 8483.20.40.40                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | SAF 1511/C3                    |
| Weight / LBS                  | 16                             |
| Nominal Bolt Center to Center | 7.6 Inch   193 Millimeter      |
| B                             | 2.75 Inch   69.85 Millimeter   |
| d                             | 1.938 Inch   49.225 Millimeter |
| Bolt Spacing Minimum          | 7.375 Inch   187.325Millimeter |
| D                             | 3.875 Inch   98.425 Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| Bolt Spacing Maximum          | 7.875 Inch   200.025Millimeter |