SKF FY 25 FM bearing units

With over 10170 full-service stores, our SKF FY 25 FM bearing units inventory is extensive and our 9 Days or more Days to Ship parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars. Double Shielded Bearing Style

Days to Ship	9 Days or more
RoHS	6
Bearing Style	Double Shielded
d	75
D	105
В	16
Basic Dynamic Load Rating Cr(N)	20800
Allowable Rotational Velocity(Grease Lubrication)(rpm)	6200
Basic Static Load Rating Cor(N)	19700
Sealing Structure	Double Shielded
Туре	Ball
Bearing Ring Material	Steel
Outer Ring Shape	Flat
Precision	Grade 0
Specifications, Environment	Standard
Load Type	Radial
Number of Raceway Ring Rows	Single Row
Size Standards	Metric System
Transmitter Material	Steel
Retainer Type	Punching
Inner/Outer Ring Material	[Steel] Steel

I.D.(Ø)	75
0.D.(Ø)	105
Width(mm)	16
Basic Dynamic Load Rating(N)	24400
Max. Allowed rpm(rpm)	6000
Rolling Element Material	[Steel] Steel
Basic Load Rating, Static Rating(N)	22600
Clearance sign	CN (standard)
Accuracy(Class)	Class 0
Acoustic Symbol	No
Holder Symbol	No
Symbol of Bearing Ring Shape	No
Seal, Shield Symbols	ZZ
Precision Grade Symbol	No
Special Configurations Code	No
Rubugado Symbol	No
Material Symbol	No
Spacer, Sleeve symbol	No
Types	No
Load Direction	Radial
Outer Ring	With Outer Ring
Combination symbol	No
Low Torque Specification	No
Internal Symbol	No
Torque Symbol	No
Specifications/Environment	Standard