

SKF FYR 3 7/16 bearing units

What is SKF FYR 3 7/16 bearing units in mechanical engineering? Manufacturing Service . Upload your CAD file for an instant. 60.325 mm da

da	60.325 mm
Da	160 mm
Ca	64.795 mm
A1	98.425 mm
A2	223.838 mm
S	4.763 mm
ba	44.45 mm
H	192.088 mm
H1	101.6 mm
H2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
J1	53.975 mm
L	349.25 mm
N1	19.05 mm
R1	60.325 mm
R2	27.94 mm
RG	3/8 NPT
PG	1/8 NPT
h	40.481 mm
Housing	FSAF 615
Bearing	22315 EK
Adapter sleeve assembly	SNW 115×2.3/8

Stabilizing ring	SR-18-15
Taconite seal	TER 36
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1250 r/min
P60°	101 kN
P90°	60.9 kN
P120°	38.3 kN
P150°	34.7 kN
P180°	42.3 kN
Pa	12.5 kN
Mass pillow block	23.6 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	141.75 g