

# SKF FYT 1/2 RM bearing units

How do N/A Minimum Buy Quantity you find the SKF FYT 1/2 RM bearing units specification? Manufacturers Online Free check 0.0 Inventory

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 57.204   |
| EAN                       | 0883450287135  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | V Lock   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 1 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22226  |
| Seals                     | Triple Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Single Nut   SAF Style  |
| Long Description          | 2 Bolt Pillow Block; 115MM Bore; 152.4MM Base to Center Height; V Lock Mount; Spherical Roller Beari |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | QVPA26V115SEN                  |
| Weight / LBS                  | 126                            |
| D                             | 5.82 Inch   147.828 Millimeter |
| Bolt Spacing Maximum          | 15.75 Inch   400.05Millimeter  |
| d                             | 4.528 Inch   115 Millimeter    |
| Nominal Bolt Center to Center | 15 Inch   381 Millimeter       |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| Bolt Spacing Minimum          | 14.25 Inch   361.95Millimeter  |
| B                             | 6 Inch   152.4 Millimeter      |