

SKF GEZ208ES-2LS plain bearings

With over 10170 full-service stores, our SKF GEZ208ES-2LS plain bearings inventory is extensive 20 mm d and our parts are priced right. within 14 mm B 24 hours. This helps you 47 mm D maximize your productivity by saving time and your hard-earned dollars.

d	20 mm
D	47 mm
B	14 mm
a min	2.31 mm
a max	2.46 mm
rs min	1 mm
rNs min	0.5 mm
D3 max	44.6 mm
b min	1.35 mm
b max	1.65 mm
r0 max	0.4 mm
Radial clearance class	C3
Mass	0.11 kg
Dynamic load, C	12.8 kN
Static load, C0	6.65 kN
Fatigue limit load, Cu	0.3 kN
f0	13.2
Nlim (grease)	16,000 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	180 °C

Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.12 Hz
Characteristic outer ring frequency, BPF0	3.08 Hz
Characteristic inner ring frequency, BRFI	4.92 Hz
da min	25 mm
Da max	42 mm
ra max	1 mm
rNa max	0.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.106
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO

Other Features	Deep Groove With Snap Ring Groove Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.234
Outside Diameter	1.85 Inch 47 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	0.787 Inch 20 Millimeter
Outer Race Width	0.551 Inch 14 Millimeter