

SKF GEZM 408 ES-2RS plain bearings

We work closely with our 20 Bore Diameter (mm) SKF GEZM 408 ES-2RS plain bearings manufacturing partners to bring the best value 20 mm d to customers.

Bore Diameter (mm)	20
d	20 mm
s1	24 mm
A	32 mm
A1	23 mm
B1	31 mm
G	10 mm
H	56 mm
H1	28.4 mm
H2	3.2 mm
J	86 mm
L	108 mm
N	11,2 mm
Weight	0,28 Kg
Basic dynamic load rating (C)	12,7 kN
Basic static load rating (C0)	6,55 kN
Housing material	Pressed steel
Basic dynamic load rating C	12.7 kN
Basic static load rating C0	6.55 kN
Fatigue load limit Pu	0.28 kN
Permissible radial housing load max.	1.8 kN
Limiting speed	8500 r/min

Mass bearing unit	0.29 kg
Thread grub screw G2	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in
Housing	P 52
Bearing	YET 204
Rubber seating ring	RIS 204